

Color Dome Camera

MTC-808DHQ, MTC-808DH, MTC-805D

FEATURE



◆ Black or Ivory Finish Available

MTC-808DHQ

1/3" Super Hi-Res.
Color Dome Camera
SONY HQ1
540TVL/ 0.5Lux@F2.0




MTC-808DH ^{new}

1/3" Hi-Res.
Color Dome Camera
480TVL/ 0.5Lux@F2.0



MTC-805D

1/3" Med-Res.
Color Dome Camera
420TVL/ 0.3Lux@F2.0



Tol: ± 0.5 Unit:mm

SPECIFICATIONS

	MTC-808DHQ		MTC-808DH		MTC-805D	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
TV System	PAL	NTSC	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY Super HAD CCD					
Number of Total Pixels	795(H) X 596(V)	811(H) X 508(V)	795(H) X 596(V)	811(H) X 508(V)	537(H) X 597(V)	537(H) X 505(V)
Synchronizing System	Internal					
Resolution	540 TVL		480 TVL		420 TVL	
Minimum Illumination	0.5Lux@F2.0		0.35Lux@F2.0		0.3Lux@F2.0	
Gain Control	Automatic					
Electronic Shutter Speed Mode	Automatic, 1/50(60)sec. ~1/100,000sec.					
Back Light Compensation	Automatic					
Signal to Noise Ratio	More than 50dB(AGC Off)					
Video Output	1Vp-p Composite / 75Ω					
White Balance	AWB					
Power Supply	12Vdc					
Power Consumption	1.7W		1.3W		1.1W	
Lens/Angle of view(H)	Standard: f3.6mm/F2.0 / 72.5° Options: f2.5mm/88°, f6.0mm/47.5°, f8.0mm/36.5°, f12.0mm/24.5°, f16.0mm/17.5°					
Operation Temperature	-10°C ~ +50°C					
Operation Humidity	RH85% or less					
Storage Temperature	-20°C ~ +60°C					
Dimensions	112(DIA) X 70(H) mm					
Weight	220g					

